

LISTING OF CLAIMS

This listing of claims replaces all prior versions, and listings, of claims in the application:

- 1 1. – 9. (Cancelled)
- 1 10. (Previously Presented) A method for maintaining secure network connections, the
2 method comprising:
3 duplicating, at a third network element, a security association associated with a secure
4 network connection between a first network element and a second network element, wherein a
5 lookup of the security association associated with the secure network connection is not
6 dependent on any destination address; and
7 in response to detecting failure of the second network element, replacing the second
8 network element with the third network element in the secure network connection with the first
9 network element, wherein the secure network connection between the first network element and
10 the third network element is based on the duplicated security association.
- 1 11. (Previously Presented) The method according to claim 10 further comprising sending at
2 least one secure message from the third network element to the first network element to notify
3 the first network element that the secure network connection will be taken over by the third
4 network element.
- 1 12. (Previously Presented) A method for maintaining secure network connections, the
2 method comprising:
3 configuring a plurality of security gateways such that a lookup of security associations is
4 not dependent on any destination address; and
5 sharing a security association among the plurality of security gateways.
- 1 13. (Cancelled)
- 1 14. (Previously Presented) The first security server according to claim 22, wherein a lookup
2 of security associations is not dependent on any destination address.

1 15. – 16. (Cancelled)

1 17. (Previously Presented) The first security server according to claim 22, wherein
2 communications between the mobile client and the first security server are based on a security
3 architecture for the internet protocol (IPsec).

1 18. – 19. (Cancelled)

1 20. (Previously Presented) The method of claim 10, further comprising:
2 during life of the secure network connection between the first and second network
3 elements, the third network element receiving information relating to the security association of
4 the secure network connection from the second network element.

1 21. (Previously Presented) The method of claim 20, wherein the first network element is a
2 mobile client, and the second and third network elements are security servers.

1 22. (Previously Presented) A first security server comprising:
2 a transceiver to receive information relating to at least one security association of a secure
3 network connection between a mobile client and a second security server; and
4 a processor module to:
5 monitor operation of the second security server;
6 in response to detecting failure of the second security server, send a message to
7 the mobile client that the first security server is taking over the secure network connection; and
8 communicate with the mobile client using the at least one security association
9 over the secure network connection between the first security server and the mobile client.

1 23. (Previously Presented) The method of claim 10, wherein the first network element is a
2 mobile client, and the second and third network elements are security servers.

1 24. (Previously Presented) The first security server of claim 22, wherein information relating
2 to the at least one security association is duplicated at the first and second security servers.

1 25. (Previously Presented) The method of claim 12, wherein sharing the security association
2 comprises sharing an IPsec security association among the plurality of security gateways.